

It's Your Money! Make a single investment and never replace failed pipe again!



316L stainless steel primary pipe Compatible with all current and future fuels Only underground fuel pipe to pass 2 hour fire test Continuous double wall pipe Easy to install - no gluing or weather delays No polyethylene - no growing pipe 30 year warranty on pipe and fittings







doubletrac.net

DOUBLETRAC FEATURES AND BENEFITS FOR RETAIL APPLICATIONS

DURABILITY

- 316L Stainless steel primary good for all blends of ethanol, bio-fuels and DEF, no need to change out pipe for future fuel, additives or ethanol blends
- Mechanical fittings do not require special tools, no welders, benders, sanding glue kits etc. stainless fittings available which contain both primary (metal-to-metal seal) and secondary seals and are reusable
- Mechanical fittings passed two hour fire test
- Interstitial space is 38 times faster than the UL minimum requirements
- .000001 GPH permeation rate, exceeds the allowable .05 GPH by 1000 times – DoubleTrac doesn't permeate!

EASE OF INSTALLATION

- Available sizes 1", 1.5" and 2" offered in rolls and sticks and can be ordered by the foot
- Fittings available with Quick Connector style ends
- Traceable when underground without a need for a tracer or locator



DoubleTrac pipe pulls easily through a 4" chase.

- Can be installed in all types of weather Bend radius at 20° F for 1'' = 12'', 1.5'' = 24'' and 2'' = 32''. Less memory than non-metallic flex pipe
- 30 year warranty on pipe and fittings for USTs with or without chase pipe
- 15 year warranty on pipe and fittings for ASTs
- Contractor on-site training included



Omega Flex, Inc. 451 Creamery Way, Exton, PA 19341-2509 Tel: 1-610-524-7272 Fax: 1-610-524-6484 Toll Free: 1-800-355-1039 DBT-181 / REV 11/19 © Omega Flex, Inc. 2019

OmegaFlex.