



# UL listed Flexible Connector by OmegaFlex®

- UL 2039 Listed
- NFPA 30/30A Compliant
- 100% Tested Using a Helium Mass Spectrometer
- Full Vacuum Rated
- Made in the USA
- 1 Year Warranty
- End Fittings are all Stainless Steel Construction
- Compatible with all Fuel Types, Ethanol's & Bio-Fuels
- Compatible with DEF using Standard Flex Connectors
- Piping is 316L stainless steel, Braid is 304L stainless steel
- Use with DoubleTrac® SF flange fittings for time savings installation
- 36" long Heat Shrink Isolation Sleeve available in 2 sizes



| O-Flex Connector Size | Max Allowable Working Pressure | Minimum Centerline Static Bend Radius | Nominal O.D. |
|-----------------------|--------------------------------|---------------------------------------|--------------|
| 3/4"                  | 200psi                         | 4"                                    | 1.10"        |
| 1"                    | 100psi                         | 4.5"                                  | 1.42"        |
| 1 1/2"                | 100psi                         | 4.5"                                  | 1.95"        |
| 2"                    | 100psi                         | 5"                                    | 2.58"        |
| 3"                    | 100psi                         | 7.5"                                  | 4.01"        |

Custom lengths up to 12 feet available with lead time.

3/4" to 3" Hex Male NPT threads both ends 12" to 36" overall lengths

3/4" to 3" Hex Male X SF Flange 12" to 36" overall lengths

3/4" to 3" Hex male X SF Flange with: Male or Female adapter, clamp and O-ring 12" to 36" overall lengths

1 1/2" and 2" Male and Female NPT X Male and Female swivel NPT 12" to 24" overall lengths



## UL listed Flexible Connector by OmegaFlex®

1 1/2" and 2" inch tees and elbows with SF Flanges, FRP female glue adapter, male or Female NPT adapter. Tee and Elbow can be welded or clamped to the Flex Connector. Overall lengths from 12" to 30". Clamps, O-rings, Tees, Elbows, Male, Female NPT Adapters, and Female FRP Adapters are also sold separately. 36" long Heat Shrink Isolation Sleeve available in 2 sizes.

[www.doubletrac.net](http://www.doubletrac.net)



Omega Flex, Inc.

451 Creamery Way, Exton, PA 19341-2509

Tel: 1-610-524-7272 Fax: 1-610-524-6484

Toll Free: 1-800-355-1039

DBT-191 Rev 06/20

© Omega Flex, Inc. 2020